

TR11 Track

Surface



Low Profile Surface Track powder-coated in black, RAL9005




Low Profile Surface Track powder-coated in white, RAL9003




Low Profile 48V track

- PC/PVC extruded insulation with 4 copper conductors(2 conductors for data signal like DALI).
- Extruded aluminum shell with powder-coated finishings.
- The linear extruded cover to make the coppers and insulations concealed.




TR11.01.A
PC extruded insulation




TR11.01.B
PVC extruded insulation

Lengths

L=1000 / 2000



L=1000 mm



L=2000 mm

TR11.01 Tracks




Insulation	Finishing	Length	Order Code
PC	White	1000mm	TR11.01.A.WH1
PC	White	2000mm	TR11.01.A.WH2
PC	Black	1000mm	TR11.01.A.BK1
PC	Black	2000mm	TR11.01.A.BK2
PVC	White	1000mm	TR11.01.B.WH1
PVC	White	2000mm	TR11.01.B.WH2
PVC	Black	1000mm	TR11.01.B.BK1
PVC	Black	2000mm	TR11.01.B.BK2

TR11.01C1 Tracks



Insulation	Finishing	Radius	Order Code
PC	White	R300mm	TR11.01C1.A.WH300
PC	White	R450mm	TR11.01C1.A.WH450
PC	Black	R300mm	TR11.01C1.A.BK300
PC	Black	R450mm	TR11.01C1.A.BK450
PVC	White	R300mm	TR11.01C1.B.WH300
PVC	White	R450mm	TR11.01C1.B.WH450
PVC	Black	R300mm	TR11.01C1.B.BK300
PVC	Black	R450mm	TR11.01C1.B.BK450



TR11.01C2 Tracks



Insulation	Finishing	Radius	Order Code
PC	White	R300mm	TR11.01C2.A.WH300
PC	White	R450mm	TR11.01C2.A.WH450
PC	Black	R300mm	TR11.01C2.A.BK300
PC	Black	R450mm	TR11.01C2.A.BK450
PVC	White	R300mm	TR11.01C2.B.WH300
PVC	White	R450mm	TR11.01C2.B.WH450
PVC	Black	R300mm	TR11.01C2.B.BK300
PVC	Black	R450mm	TR11.01C2.B.BK450

