

TR11 Track

Trimless



Trimless Track in black



Trimless Track in black


•One track with two methods of installation via removable leave






High Profile Trimless 48V Tracks

- PC/PVC extruded insulation with 4 copper conductors(2 conductors for data signal like DALI)
- Extruded aluminum shell with powder-coated finishings
- Removable leaves to get two methods of installations
- The linear extruded cover to make the coppers and insulations concealed



TR11.03.A
PC extruded insulation

•removable leaves for two kinds of installations



TR11.03.B
PVC extruded insulation

Lengths
L=1000 / 2000



L=1000 mm




L=2000 mm


TR11.03 Tracks



Insulation	Finishing	Length	Order Code
PC	White	1000mm	TR11.03.A.WH1
PC	White	2000mm	TR11.03.A.WH2
PC	Black	1000mm	TR11.03.A.BK1
PC	Black	2000mm	TR11.03.A.BK2
PVC	White	1000mm	TR11.03.B.WH1
PVC	White	2000mm	TR11.03.B.WH2
PVC	Black	1000mm	TR11.03.B.BK1
PVC	Black	2000mm	TR11.03.B.BK2



TR11.03.A



TR11.03.B

TR11.03C Tracks



Insulation	Finishing	Radius	Order Code
PC	White	R300mm	TR11.03C.A.WH300
PC	White	R450mm	TR11.03C.A.WH450
PC	Black	R300mm	TR11.03C.A.BK300
PC	Black	R450mm	TR11.03C.A.BK450
PVC	White	R300mm	TR11.03C.B.WH300
PVC	White	R450mm	TR11.03C.B.WH450
PVC	Black	R300mm	TR11.03C.B.BK300
PVC	Black	R450mm	TR11.03C.B.BK450

