

# NES-P

APPLICATIONS:  
Open-plan office, training room,  
conference room and other office spaces.



Microprism  
UGR<19

Direct and indirect  
lighting with impressive  
light uniformity

Support DALI and  
1-10V dimming


## PRODUCT PARAMETERS

Luminaire Wattage	50W	60W
Luminous Flux	6350lm	7500lm
CCT	3000K / 4000K / 6000K	
CRI	>80	
UGR	<19	
Protection Rating	IP20	
Longevity	50,000Hrs L80 B10	
Function	On/off / 1-10V dimming / DALI dimming	
Colours	Silver / White / Black	
Warranty	5 years	

## PRODUCT MODEL

Part No.	LM	Power	Function
NES-P-50	↑ 2700lm/3650lm ↓	↑ 20W/30W ↓	On/off
NES-P-50-1-10V	↑ 2700lm/3650lm ↓	↑ 20W/30W ↓	1-10V dimming
NES-P-50-DALI	↑ 2700lm/3650lm ↓	↑ 20W/30W ↓	DALI dimming
NES-P-60	↑ 3000lm/4500lm ↓	↑ 24W/36W ↓	On/off
NES-P-60-1-10V	↑ 3000lm/4500lm ↓	↑ 24W/36W ↓	1-10V dimming
NES-P-60-DALI	↑ 3000lm/4500lm ↓	↑ 24W/36W ↓	DALI dimming

## SIZE



## LIGHT DISTRIBUTION

