

Multi-dots & Linear



CASAMBI



- Complete with adapter for installation on 48V low voltage tracks.
- Die cast aluminum body without the annoyance from the extruded aluminum end caps.
- The plastic adapter integrated with the DC / DC converters available in DALI, Casambi, phase-cut, 0-10V dimmable options.
- Grille mini optics made of thermoplastic material, integrated in the innovative black antiglare screen that defines emission with glare control UGR<10.
- Linear mini light system with PC cover is an ideal choice for floodlight application.


Optics



TR11.M15



source W	system W	lm/W	optic	CRI
5.4W	6.5W	55lm/W	55°	> 90
CCT				
2700K/3000K/4000K				
Finishing				
White/Black				





TR11.M16



source W	system W	lm/W	optic	CRI
9W	10.5W	55lm/W	55°	> 90
CCT				
2700K/3000K/4000K				
Finishing				
White/Black				

TR11.M17



source W	system W	lm/W	optic	CRI
9W	10.5W	55lm/W	60°	> 90
CCT				
2700K/3000K/4000K				
Finishing				
White/Black				

TR11.M18



source W	system W	lm/W	optic	CRI
12.5W	15W	55lm/W	55°	> 90
CCT				
2700K/3000K/4000K				
Finishing				
White/Black				

TR11.M19



source W	system W	lm/W	optic	CRI
12.5W	15W	55lm/W	60°	> 90
CCT				
2700K/3000K/4000K				
Finishing				
White/Black				