

Tube 40 Wallwash



TR11.M6




| source W | system W | lm/W | optic | CRI |
|----------|----------|---------|----------|------|
| 5.4W | 6.5W | 101lm/W | wallwash | > 90 |
| 9W | 10.5W | 101lm/W | wallwash | > 90 |


CCT
2700K/3000K/4000K/1800-4000K/2700K-6500K

Finishing(base)
White/Black

Finishing(tube)
P01-P05; A01-A10; EP01-EP04



TR11.M6



TR11.M6-1
(long-stem for high profile tracks)

CASAMBI



- The innovative wall washer optic was designed to ensure uniform lighting of walls from the highest to the lowest points, as well as avoiding shadow areas in zones near the ceiling.
- Advanced Dimming Options: The plastic adapter features built-in DC/DC converters, offering DALI, Casambi, phase-cut, and 0-10V dimmable solutions. With an integrated Casambi module, enjoy independent control over dimming and switching for each spotlight.

- Effortless Installation: The fast-acting mechanical and electrical connection system ensures tool-free installation onto the track.
- Premium Finish Options: Available in classic sand black/white, high-gloss black/blue/rose with PVD coatings, or luxurious brushed champagne, bronze, and gold anodized finishes to complement any design aesthetic.

Optics

The innovative wall washer optic was designed to ensure uniform lighting of walls, from the highest to the lowest points, as well as avoiding shadow areas in zones near the ceiling.



Correct installation

Correct installation distances to achieve uniform lighting of the walls. For installation criteria, refer to the instruction sheet.

